



**Specifications Philips LED Panel  
FlexBlend SP342P 37,5W 4500lm - 940  
Cool White | 150x20cm - UGR <25 -  
Dali Dimmable - Best Colour  
Rendering**

[View Product](#)

## General Information

|                          |                                  |
|--------------------------|----------------------------------|
| SKU                      | 238840                           |
| EAN                      | 8719514103788                    |
| manufacturer_code        | 10378800                         |
| Brand                    | Philips                          |
| Manufacturer Name        | SP342P 45S/940 PSD O SMT L150 WH |
| Any Lamp all-in warranty | 5 Years                          |
| Average Lifetime (h)     | 50000                            |
| Series                   | SP342P                           |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 2x58               |
| Wattage                     | 37.5W              |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 940 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 90-99              |
| Colour of Light             | White              |
| Light Colour Options        | Single Color       |

|                        |                   |
|------------------------|-------------------|
| Luminous Flux (Lumen)  | 4500lm            |
| Lumen per watt         | 120               |
| IP-Rating              | IP20              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Fixture Connection     | Terminal, 5-pole  |
| Driver Included        | Yes               |
| Power factor           | >0.90             |
| Product Type Category  | LED Panel         |

## Fixture Information

---

|                       |                                    |
|-----------------------|------------------------------------|
| EOC8                  | 10378800                           |
| Mounting Method       | Suspendu                           |
| Unified Glare Rating  | < 25 - for hallways and staircases |
| Optical Cover         | PC (Polycarbonate)                 |
| Operating Temperature | -10 to +40                         |
| Emergency Lighting    | No Emergency Unit                  |
| Colour of the Fixture | White                              |
| Housing               | Steel                              |
| Colour of material    | White                              |

## Dimensions

---

|                |          |
|----------------|----------|
| LED panel size | 150x20cm |
| Length (mm)    | 1470     |
| Width (mm)     | 200      |
| Height (mm)    | 73       |

## Sensor Information

---

Type of sensor

No Sensor

### Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

